

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Heated display case (with or without climate)
Name and address of the applicant	AKE Ausseer Kälte- und Edelstahltechnik GmbH Pichl 66 8984 Bad Mitterndorf Austria
Name and address of the manufacturer	AKE Ausseer Kälte- und Edelstahltechnik GmbH Pichl 66 8984 Bad Mitterndorf Austria
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 AKE Ausseer Kälte- und Edelstahltechnik GmbH Pichl 66 8984 Bad Mitterndorf Austria
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	50/60 Hz, IPX4, class I Caleo Basic 120: 4,00 kW, 400 VAC Caleo Basic 60: 2,74 kW, 220-240 VAC Caleo Basic 80: 3,01 kW, 220-240 VAC Caleo Hot 120: 2,85 kW, 220-240 VAC Caleo Hot 142: 3,73 kW, 400 VAC Caleo Hot 60: 1,68 kW, 220-240 VAC Caleo Hot 80: 2,05 kW, 220-240 VAC
Trademark (if any)	AKE
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	Caleo Basic 120, Caleo Basic 60, Caleo Basic 80, Caleo Hot 120, Caleo Hot 142, Caleo Hot 60, Caleo Hot 80
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2 See the Appendix.
A sample of the product was tested and found to be in conformity with	IEC 60335-1:2010, IEC 60335-1:2010/AMD1:2013, IEC 60335-1:2010/AMD2:2016, IEC 60335-2-49:2002, IEC 60335-2-49:2002/AMD1:2008, IEC 60335-2-49:2002/AMD2:2017 National differences: EU Group Differences, AU, NZ
As shown in the Test Report Ref. No. which forms part of this Certificate	TR_2021633_1

This CB Test Certificate is issued by the National Certification Body


SGS Belgium N.V. – Division SGS-CEBEC
Riverside Business Park, Bld Internationalelaan 55, Build. K, BE-1070 BRUSSELS,
Belgium

Signature: Calogero Lana

Date: 2022-02-03

BE-10322 - Appendix**General product information:**

Trade mark	Models	Rated voltage and frequency	Rated power	Degree of protection	Ingress protection
AKE	Caleo Basic 60	220-240 V~ 50/60 Hz	2,74 kW	Class I	IPX4
	Caleo Basic 80	220-240 V~ 50/60 Hz	3,01 kW		
	Caleo Basic 120	400 V~ 50/60 Hz	4,00 kW		
	Caleo Hot 60	220-240V ~ 50/60 Hz	1,68 kW		
	Caleo Hot 80	220-240V ~ 50/60 Hz	2,05 kW		
	Caleo Hot 120	220-240V ~ 50/60 Hz	2,85 kW		
	Caleo Hot 142	400V ~ 50/60 Hz	3,73 kW		



Ref. Certif. No.

SE-107720

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Commercial Refrigeration appliances
Name and address of the applicant	AKE Ausseer Kälte- und Edelstahltechnik GmbH Pichl 66 8984 Bad Mitterndorf Austria
Name and address of the manufacturer	Same as applicant
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	Same as applicant
Ratings and principal characteristics	See page 2
Trademark (if any)	AKE
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	Caleo *** ** * * *
Additional information (if necessary may also be reported on page 2)	See page 2
A sample of the product was tested and found to be in conformity with	IEC 60335-1:2010+A1+A2 IEC 60335-2-89:2019
As shown in the Test Report Ref. No. which forms part of this Certificate	2245371KAU-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden



Signature: *Quan Li*

Date: 11 April, 2022

Quan Li

Ratings and principal characteristics

220-240V AC, 50Hz

Model	Max. power input (W)	Max. current input (A)
Caleo *** ** *		
Caleo Cold 60	--	3.90
Caleo Cold 80	--	4.0
Caleo Cold 120	--	4.20
Caleo Neutral 60	--	0.1
Caleo Neutral 80	--	0.1
Caleo Neutral 120	--	0.24
Caleo Neutral 142	--	0.28
Caleo Neutral 60 Plus	--	0.1
Caleo Neutral 80 Plus	--	0.1
Caleo Neutral 120 Plus	--	0.24
Caleo Neutral 142 Plus	--	0.28

Additional information

Description of the model Caleo *** ** *:

The 1st, 2nd, 3rd symbol can be: Cold (complete device) or Neutral (without refrigeration circuit)The 4th, 5th, 6th symbol can be: 60, 80, 120, 142 (width of appliance, 142 only Neutral / Neutral Plus)The 7th, 8th, 9th symbol can be: blank or Plus (additional glass in display area)The 10th symbol can be blank or Z (remote refrigerated)

The products have been checked according to the following standards:

EN 60335 1:2012 + AC:2014 + A11:2014 + A13:2017 + A1:2019 + A14:2019 + A2:2019

EN 60335-2-89:2010 + A1:2016 + A2:2017 used in conjunction with EN 60335-1:2012 + A11:2014 + A13:2017

AS/NZS 60335.1:2020

AS/NZS 60335.2.89:2020

Date: 11 April, 2022

Signature: 